

# Maximum-Stretch

## 12-YEAR METAL ROOF GUARANTEE

### A NO PEEL WARRANTY

When applied on metal this product is warranted to not peel for a period of twelve years from date of application when used according to label application instructions with good construction methods over a savable metal roof with proper drainage. Surface must be clean, bare, dry and rust free.

At the sole discretion of Ames, Ames Research Laboratories will, with proof of purchase, replace the defective product with product of an equal value on a pro-rated basis or Ames will provide a buy one get one free option.

The application shall consist of the following steps:

#### First step condition of application.

Clean the roof off properly and seam tape all joints with Ames Peel and Stick seam tape. Apply Ames Peel & Stick Contouring Self Adhesive Rubber Seam Tape (PS250, PS450, PS650) to all seams and joints. Seam tape around all skylights, and around all vents and where ever there are two types of metal or surfaces such as vents, wood to plastic or plastic to metal or whatever the gap may be or require.

The user will purchase and apply a minimum of two gallons per 100 sq. ft. of Ames roof coating on the first coat. For rusted metal surface, apply a second additional coat of one gallon per 100 sq. ft. of Ames roof coating as needed.

#### Second Step.

Upon Five (5) Years Continuing Preventative maintenance shall be performed over the entire roof that consists of an additional one (1) gallon per 100 sq. ft. of Ames Roof coating. To extend the warranty to seven (7) years period as needed.

At the end of the seventh year the user if needed will give Additional Continuing Preventative Maintenance that shall be performed by applying Ames Maximum Stretch at the rate of one (1) gallon per 100 sq. ft. over the entire roof.

This warranty in no way implies replacement due to product failure from improper application. This warranty in no way implies replacement of product due to mechanical damage due to acts of God.

This warranty does not cover damage from acts of God; such as, hurricanes, hail damage, tomadoes, or factors of nature and can nullify this warranty.

This warranty does not include labor or the cost of labor for the application of coating. This warranty applies only to the distributor or purchaser of the product and cannot be extended to any other person. Since the manner and conditions of application are beyond our control neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use or inability to use this product. Since the product must be applied in the proper place to stop the passage of moisture, the manufacturer makes no warranty for application or applicators inability to apply the product properly to achieve a proper seal.

The product shall be applied on a clean, dry surface, in a closed, continuous, unbroken film at no less than 30 dry mils of coating thickness, which is your assurance of a closed seal when properly applied. Frozen product will solidify and is not covered under product defect warranty. This warranty gives you specific legal rights, and you may also have other rights, which may vary from state to state.

No warrantee is made of the applications ability or inability to apply the product properly or for misjudgment on inclement weather conditions.



## Ames Research Laboratories, Inc.

Mailing Address:  
1891 16th St. SE.  
Salem, OR 97302 USA

Factory & Shipping Address:  
1891 16th Street SE  
Salem, OR 97302 USA